

AFM 21

TENDER SPECIFICATION

Manufacturer information

Getzner Werkstoffe GmbH
Herrenau 5
A-6706 Bürs
Austria
www.getzner.com

Brand: **Acoustic Floor Mat 21 - mat out of polyurethane (PU) granulate**

Product properties

Application:	impact sound insulation for use under floating screeds and dry screeds	
Impact sound improvement ΔL_w :	≥ 21 dB (measured acc. to EN 10140-3 with evaluation acc. EN 717-2)	
Consisting of:	mat made of recycled polyurethane granules; free from plasticizers and substances hazardous to health;	
Standard form of delivery, mats:	width	1.200 mm
	length	1.500 mm
Thickness:	8 mm	
Load range:	2.500 kg/m ²	
Dynamic stiffness s'_t :	≤ 40 MN/m ³	(measured acc. to EN 29052-1)
Compressibility c:	≤ 1 mm	(measured acc. to EN 12431)
European Technical Assessment:	ETA-20/0712	

The impact sound insulation mat is to be laid butt-jointed and bonded together at the joints using suitable adhesive tape.

A European Technical Assessment (ETA) must be submitted for deviating products.

Offered product: Acoustic Floor Mat 21 - mat out of polyurethane (PU) granulate from Getzner Werkstoffe GmbH or equal.

Quantity: m²

Sum: €
