

# Isotop® DSD-BL

## TENDER SPECIFICATION

---

### Manufacturer information

Getzner Werkstoffe GmbH  
Herrenau 5  
A-6706 Bürs  
Austria  
www.getzner.com

---

Brand: **Isotop® DSD-BL - Steel spring block element with Sylodamp® damping core**

---

### Product properties

Application:	For isolating structure-borne noise and vibrations
Efficiency of isolation	>98% (based on an excitation frequency of 50 Hz or 3000 rpm)
Consisting of:	Isotop® DSD - steel spring isolators with Sylodamp® damping core, CDC-coated Damping core on polyurethane basis, free of plasticisers and substances hazardous to health (e.g. VOC) 6 mm steel top plate and base plate, black powder-coated Top plate and base plate with 4 mm Sylomer® anti-slip plate Optionally with Isotop® DT
Natural frequency:	from 4.0 Hz = 240 min <sup>-1</sup>
Maximum load bearing:	from 400 kg to 5850 kg
For the bearing of:	_____
Total weight:	_____ kg
Excitation frequency:	_____ Hz or _____ min <sup>-1</sup>

Arrangement of vibration isolators as per the manufacturer's specifications.

Offered product: Isotop® DSD-BL from Getzner Werkstoffe GmbH or equal.

---

Quantity: ..... pcs

**Sum:** ..... €

---